

LA-UR 94-3820

CONF-950570--1

Los Alamos National Laboratory is operated by the University of California for the United States Department of Energy under contract W-7405-ENG-36

TITLE: FRACTURE COATINGS IN TOPOPAH SPRING TUFF ALONG DRILL HOLE WASH

AUTHOR(S): Barbara Carlos, EES-1
Steve J. Chipera, EES-1
David L. Bish, EES-1

SUBMITTED TO: 1995 International High-Level Radioactive Waste Management
Conference
May 1-5, 1995
Las Vegas, NV

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

By acceptance of this article, the publisher recognizes that the U.S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes.

The Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

Fracture Coatings in Topopah Spring Tuff along Drill Hole Wash

Barbara A. Carlos, Steve J. Chipera, and David L. Bish, Los Alamos National Laboratory

Introduction

Fracture-lining minerals are being studied as part of site characterization to determine the suitability of Yucca Mountain, Nevada as a potential high level nuclear waste repository. Fracture coatings in the Paintbrush Group provide information on potential flow paths above the water table both toward and away from the potential repository and provide information on the distribution of fracture-lining minerals needed to model thermal effects of waste emplacement. Fracture coatings within the predominantly non-zeolitic Paintbrush Group vary both with depth and laterally across Yucca Mountain, whereas fracture coatings in tuffs below the Paintbrush Group are related to the mineralogy of the tuffs and follow a consistent pattern of distribution with predominantly quartz, calcite, and manganese oxides in the devitrified intervals and mordenite and clinoptilolite in the zeolitic intervals (1). The zeolites stellerite and heulandite are more abundant in fractures in the Topopah Spring Tuff in drill holes USW G-1 and UE-25 a#1, located along Drill Hole Wash (at the northern end of Yucca Mountain, Figure 1), than in core from other parts of Yucca Mountain. Buesch et al. (2) present evidence for a complex fault system along Drill Hole Wash. To investigate the possibility that the abundant fracture-lining zeolites in USW G-1 and UE-25 a#1 are related to the Drill Hole Wash fault, the Topopah Spring Tuff was examined in drill cores from USW UZ-14, USW G-1, USW NRG-77a, and UE-25 a#1.

Methods

Fracture coatings were examined at up to 50 \times magnification and representative samples were scraped for X-ray diffraction analysis, which was performed with an automated Siemens D-500 powder diffractometer and Cu K α radiation. Fragments from selected fractures were examined using an ISI scanning electron microscope with EDX capabilities and a Tracor Northern ADEM SEM.

Results

Fracture-coatings in USW UZ-14 and USW G-1 are very similar (Figure 2). Prismatic zeolites (heulandite and/or stellerite) are abundant throughout most of the devitrified Topopah Spring Tuff. Heulandite occurs higher in the drill holes than stellerite and occurs sporadically with stellerite over the rest of the devitrified interval. Calcite coats one or two fractures within any 30 m interval of devitrified Topopah Spring Tuff. Drill hole UE-25 a#1 fractures contain widespread calcite, and prismatic zeolites coat fractures in the lower 90 m of the devitrified Topopah Spring Tuff, although stellerite was not identified in XRD analyses. USW NRG-77a, unlike the other drill holes, contains almost no calcite in fractures, and heulandite is limited to the 25 m immediately above the vitrophyre. No stellerite was identified in this core.

Discussion

Although prismatic zeolites are most abundant in USW G-1 and USW UZ-14, the proposed trace of the Drill Hole Wash fault (2) turns north out of Drill Hole Wash and does not pass close to these drill holes. UE-25 a#1, which is near the trace of the fault, contains abundant heulandite in the lower part of the Topopah Spring Tuff, but USW NRG-77a, which is also near the proposed fault, contains the least calcite of any drill core examined to date, no stellerite and very little heulandite. USW NRG-77a is also located near an extension of the Ghost Dance Fault and

intersects much shattered and broken rock, which intuitively should have provided transport pathways and allowed deposition of calcite and zeolites, but which does not contain these minerals. Either this shattered rock did not provide transport pathways, or flow through these fractures was so unimpeded that fluid drained quickly and minerals did not precipitate.

Conclusions

The abundant stellerite in USW G-1 and USW UZ-14 was not caused by proximity to Drill Hole Wash or any related structure. The presence of shattered and/or broken rock, presumably related to faulting, does not necessarily correlate with deposition of calcite or zeolites. This lack of correlation may indicate that these shattered zones were not transport pathways, or alternatively, that fluid transport was so rapid that no minerals were deposited. Additional studies are required to determine the factors controlling calcite and zeolite deposition in fractures in the Topopah Spring Tuff.

Acknowledgments

This work was supported and managed by the U.S. Department of Energy, Yucca Mountain Site Characterization Office.

References

1. CARLOS, B., CHIPERA, S., BISH, D., and RAYMOND, R., in press, Distribution and Chemistry of Fracture-lining Zeolites at Yucca Mountain, Nevada. Conference Volume of the Zeolite '93 Conference, the 4th International Conference on the Occurrence, Properties, and Utilization of Natural Zeolites.
2. BUESCH, D. C., DICKERSON, R. P., DRAKE, R. M., and SPENGLER, R. W., 1994, Integrated geology and preliminary cross section along the north ramp of the exploratory studies facility, Yucca Mountain: Proceedings of the Fifth Annual International Conference on High Level Radioactive Waste Management, Las Vegas, Nevada, May 22-26, 1994.

Figure Captions

Figure 1. Map of the northern part of Yucca Mountain, Nevada, indicating location of core holes, outline of the proposed repository block, and major faults, including the proposed Drill Hole Wash fault. Modified from Buesch et al., (2).

Figure 2. Generalized stratigraphy and distribution of heulandite, stellerite and calcite for the drill holes included in this study. Prismatic zeolites may be heulandite and/or stellerite, and cannot be distinguished at 50× magnification. YM = Yucca Mountain Tuff, vvv = upper vitric interval of the Topopah Spring Tuff, CH = Calico Hills Formation.




Figure 1

